

Superior product line

StreetSiren S DoubleDeck Jeweller

Wireless outdoor siren with a clip lock for a branded faceplate.














What's new

Baseline StreetSiren DoubleDeck Jeweller	Superior StreetSiren S DoubleDeck Jeweller	
Jamming is detected only by the hub	Jamming is detected by both the hub and the siren	
Common battery	Enhanced battery	
Available for all PROs	Available only for accredited partners	

This is the device of the Superior product line. Superior products are advanced versions of Jeweller devices. This product line is developed for projects. Only accredited Ajax Systems partners can sell, install, and administer Superior products.



Additional promotion of security services

The main feature of StreetSiren S DoubleDeck is the Brandplate faceplate (sold separately). A security service provider can print their logo and contact information on the front panel of the siren.

The siren becomes an additional marketing channel to reach new customers like neighbours and visitors.





Jeweller communication technology

- Radio communication at a distance of up to 1,500 m in an open space
- Encryption and device authentication to prevent spoofing
- Regular polling to display current statuses of the devices



Event notifications

- Alarms of the system's devices
- Security status: armed/disarmed
- Door opening (Chime function)
- After-alarm indication



- Up to 5 years of battery life
- Low battery notifications
- Panasonic pre-installed battery

Quick installation and setup

- Pairing with a hub via QR code
- Remote control and configuration in the app
- Effortless installation and replacement

Intended certifications	Communication with control panel	Alerts	Features
EN 50131 (Grade 2)	Jeweller communication	Alarms	Types of notifications
PD 6662:2017 INCERT	technology	Acoustic	Acoustic, LED
IP54	Frequency bands	Delay When Entering/Leaving	Alarm volume
NFA2P SSF	868,0 — 868,6 MHz	Acoustic	from 85 to 113 dB
	Communication range	Security mode change	Alarm duration
Compatibility	up to 1,500 m In an open space	Acoustic, LED	from 3 s to 3 min
Hubs		Security status	Piezoelectric buzzer
Hub Plus, Hub 2 (2G), Hub 2 (4G),		LED	frequency
Hub 2 Plus, Hub Hybrid (2G),			3.5 ± 0.5 kHz
Hub Hybrid (4G)		Door opening (Chime function)	
Range extenders		Acoustic	Clip lock for the Brandplate faceplate
ReX, ReX 2		After-alarm indication	(sold separately)
		LED	
Power supply	Installation	Enclosure	Complete set
Battery	Operating temperature range	Colour	StreetSiren S DoubleDeck Jewelle
4 × CR123A	from -25°C to +60°C	white, black	SmartBracket panel with holding screw
Battery life	Operating humidity	Dimensions	4 × CR123A batteries
up to 5 years	up to 95%	200 × 200 × 55 mm	(pre-installed) Installation kit
Manufacturer	Protection class	Weight	Quick start guide
Panasonic	IP50	571 g	













For detailed information, scan the QR code or follow the link: